

Night Vision Rear/Side/Front View Camera Universal

Part No:LC-009D

120° (H=90°) For Reversing safety






Features:

●	Special For Left & Right Side View Camera
●	E-mark (E9) , CE, FCC certification
●	Waterproof rating: IP68
●	Wide view angle = 120°(Horizontal = 90°)
●	Sharp CCD/Sony CCD/Pixelplus CMOS/Aptina AHD Cmos optional
●	Mirror / Normal image switch (optional)
●	Heater built-in for -40°C~+70°C environment (optional)



Dimensional Drawing:



Specification:

LC-009D Night Vision Rear/Side/Front View Camera Universal

TV System	NTSC / PAL
Resolution	N:510 x 492pixels P:500 x 582 pixels
Image sensor	1/4" Sharp CCD
Waterproof rating	IP68
Horizontal Resolution	420TV Lines
Min illumination	0LUX(LED ON)
Power supply	12V DC
Power consumption	1.8W(@12V DC)
Current consumption	150mA
View angle	120°(D) 90°(H) 75°(V)
Operation temperature	-40°C~+70°C
Weight	250g
Dimension(W*H*D)	63*77*50mm(Camera)

LC-009D AHD Rear view / Front view camera

TV System	NTSC/PAL
Resolution	1280*960(1.2M Pixels)
Effective Pixels	1,300,000 Pixels
Image sensor	1/3" APTINA CMOS AHD 720P
Waterproof rating	IP68
Min illumination	0LUX(LED ON)
Power supply	12V DC
Power consumption	1.8W(@12V DC)
Current consumption	150mA
View angle	120°(D) / 90°(H)
Operation temperature	-40°C~+70°C
Weight	250g
Dimension(W*H*D)	63*77*50mm(Camera)






Basic Operation:



Step 2 : Adjust the camera's viewing direction, tighten two screws gradually.

Step 1 : Mounted the base on the right position.



Position Camera:

Mount camera assembly high mounted. (Centred.)




Connector Defintion:



**M12 4 pins Aviation
Female Connector**


4PIN FEMALE MATING INTERFACE



PIN#	WIRE COLOR	DESCRIPTION
1	RED	+12V
2	BLACK/SHIELD	GND
3	WHITE	AUDIO
4	YELLOW	VIDEO





**S-Video 4-pin Aviation
Male Connector**





PIN#	WIRE COLOR	DESCRIPTION
1	YELLOW	VIDEO
2	RED	+12V
3	BLUE	N.C
4	WHITE	AUDIO
5	BLACK/SHIELD	GND



RCA +DC



BNC + Dc






View Angle & Lens:

1/4" CCD Sensor (default lens = 2.5mm)								
Lens (mm)	1.7	2.5	2.8	3.6	4.3	6.0	8.0	12.0
Diagonal	133°	110°	80°	73°	63°	48°	33°	23°
Horizontal	107°	87°	65°	59°	53°	40°	28°	20°
Vertical	73°	63°	50°	45°	40°	31°	23°	15°

1/3" CCD Sensor (default lens = 2.8mm)								
Lens (mm)	2.75	2.8	New2.8	3.6	4.3	6.0	8.0	12.0
Diagonal	140°	105°	115°	93°	82°	61°	45°	30°
Horizontal	109°	85°	88°	75°	65°	50°	37°	25°
Vertical	80°	64°	68°	59°	51°	39°	29°	19°

View angle	105°	80°	75°	50°	25°
View distance	5M	10M	16M	25M	40M






Packing:


- 1.-Universal Round Camera x 1pc
- 2.-L type Allen wrench(2.5mm)



Packing box & carton dimension:



0.3kg/pc



50pcs per carton/Weight:15kg

ADD:3/F, Blcok A8, Kaida Industry Park, Qiaochang Road,Qiaotou , Dongguan , Guangdong,China.



lntech



TEL: +86-769-8118 3549
Website: www.lintechco.com

FAX: +86-769-8255 1233
Email: info@lintechco.com